



# V26G

Fan less Touch Panel PC with Intel® Socket P Core Duo Processor



**Embedded Computer Source Ges. m.b.H.**

Franz Lehargasse 17

A-2384 Breitenfurt / Wien Austria

[www.embeddedcomputersource.com](http://www.embeddedcomputersource.com)



## Features

- 26" LED backlight 1920x1080 Panel,
- Intel® Socket P Core Duo processor;
- T3100 1.9G CPU/P8400 2.26G CPU
- Intel® GM45/ICH9-M Chipset
- 2GB DDR3 800/1066 SO-DIMM (up to 4GB)
- Capacitive Touch
- 1x HDMI, 3x USB, 1x COM port, 1x DVI, 1x RJ45, 1x Mic in, 1x Line out

## Product Specification

<b>CPU</b>	Intel® (45nm P-Socket support) T3100 1.9G 1M L2/P8400 2.26G 3M L2
<b>Chipset</b>	Intel® GM45/ICH9-M chipset
<b>System Memory</b>	2GB SO-DIMM DDR3 800/1066 (up to 4GB)
<b>Display</b>	Panel size: 26" LED Backlight (TFT LCD) Brightness: 400 nits Resolution: 1920 X 1080
<b>Touch Screen</b>	Surface Capacitive Touch
<b>LAN</b>	RJ-45, Gigabit Ethernet (Intel® 82567)
<b>Expansion slot</b>	1x PCIe x4 slot(w/4x PCIe x1 speed)

**Embedded Computer Source Ges. m.b.H.**

Franz Lehargasse 17

A-2384 Breitenfurt / Wien Austria

[www.embeddedcomputersource.com](http://www.embeddedcomputersource.com)



<b>I/O Interface</b>	1x HDMI 1x Serial port RS232 3x USB connectors 1 x MIC-in 1 x Line-out 1 x DVI 1x RJ-45
<b>Storage</b>	2.5" SATA HDD 160GB
<b>Power Supply</b>	AC100~240V
<b>Audio</b>	Built-in 2x8W speaker
<b>Dimension</b>	630.5(H)*377(W)*57.1(D)mm
<b>Environmental</b>	Operation temp: 0 ~35 ° C Storage temp: -20 ~ 60°C Humidity: Operation 20%~80%; Storage 10%~80%
<b>LED</b>	Power LED
<b>Weight</b>	Main unit: 10 kg ; including packing carton: 13kg ( Appox )



<b>Option Feature</b>	WLAN Module 802.11b/g
	Table stand
	Wall Mount Kit
	Trust Stand

\*specification subject to change without prior notice

## Mechanical Drawing



